



The SUMO ST512 digital terminal integrates a vivid display with flexible computing in one slim, mountable design.

The SUMO ST512 features the integration of a bright 12" LCD display, over an efficient and powerful x86 1.5GHz-powered thin client platform.

With options for IR touch screen and internal wireless communication. The full-featured yet elegant, space-saving package accommodates a range of accessories and peripherals to support a wide variety of vertical applications.



Features

- ▶ Support for Windows® XP Embedded or Windows® XP Professional
- ▶ Integrates major thin-client/server computing protocols (Citrix ICA, Microsoft RDP), terminal emulation suite; and web browsers
- ▶ Comprehensive and intuitive remote device administration through server-based Sumo Device Manager software
- ▶ Configurable for thin-client/server computing, browser-based computing, or local application shell
- ▶ Comprehensive set of USB and full legacy I/O ports for peripherals and accessories
- ▶ VESA-mountable for flexibility in mounting and deployment
- ▶ Options for IR touch screen
- ▶ Optional integrated 802.11 a/b/g wireless LAN adapter

Applications

The Sumo ST512 is the ideal computing platform for the following applications:

- ▶ Kiosks
- ▶ Retail
- ▶ Entertainment / Gaming
- ▶ Education
- ▶ Manufacturing
- ▶ Hospitality
- ▶ Control and Monitoring
- ▶ Finance
- ▶ Healthcare

Major Options

- ▶ Built in 802.11a/b/g wireless LAN
- ▶ IR touch screen

Lower I/O Panel



Front View



Side View



Specification

▶ Operating Systems

Windows® XP Embedded
Windows® XP Professional

▶ Processor

1.5Ghz x86 processor

▶ Storage

2GB, 4GB, 8GB or 16GB flash module
2.5" Hard Disk Drive (HDD)

▶ Memory (RAM)

1GB

▶ Display

12" TFT LCD with 50,000 hours lamp life
1024 x 768 resolution

▶ Controls and Connectivity

Five side buttons - 1 Power, 4 Programmable
1 Serial port
1 Video-in RCA jack
2 USB 2.0 ports
RJ45 connector for Ethernet
1 Audio-out jack
1 Microphone-in jack
1 Line-in jack
1 DC-in jack

▶ Network interface

Ethernet 10/100 Base-T LAN
Wireless 802.11a/b/g (optional)

▶ Physical Dimensions

W x H x D
309 x 231 x 64 mm
12.1 x 9.09 x 2.51 inches

▶ Base Weight

4Kg (8.8lbs)

▶ AC/DC Adapter

Input: 100-240V AC, 50-60Hz
Output: 18.5V 3.5A

▶ Power Cords

UK, EU, North America, China

▶ Operating Environment

Temperature: 0° - 40°C
Humidity: 0% - 90% non-condensing

▶ Regulatory Compliance

FCC Class B, CE, C-Tick, RoHS Compliant



For more information, including pricing, availability and detailed features please look at our web site at www.sumotech.com or email sales@sumotech.com

SUMO Technologies Ltd, Manor Chambers, Marygate, YORK YO30 7BH
Tel: +44 (0) 1904 670670 Fax: +44 (0) 1904 670570

All specifications are subject to change without notice.

SUMO, Masters of Technology, ST512 are trademarks of SUMO Technologies Ltd. Microsoft Windows XP, Microsoft Windows XP Embedded are registered trademarks of Microsoft Corporation. All other products and services are trademarks or service marks of their respective companies, and are acknowledged. E&OE